

KS-7300 / 6600 Series

www.posiflex.com

POSIFLEX
Your Success is Our Vision



Specification	KS-6617Z	KS-6617Z-I	KS-7315G	KS-7315G-I	KS-7317Z	KS-7317Z-I
Processor	Intel Celeron M 1.0 GHz / 0 Cache CPU or Intel Celeron M 1.5 GHz / 1 M Cache CPU		Intel Celeron M 1.86 GHz / 1 MB Cache CPU or Intel Core Duo 2.0 GHz / 2 M Cache CPU or Intel Core 2 Duo 2.16 GHz / 4 M Cache CPU			
System Memory	DDR2 400 MHz, SO-DIMM x 1, max 2 G, default 1 GB		DDR2 667 MHz, SO-DIMM x 1, max 2 G, default 1 GB			
Storage Device	2.5" SATA HDD or CF Kit (Optional)					
Power Supply	12V DC power adaptor, 80W					
Audio	Built in 2 x 2W speaker, Line Out / Mic in					
OS support	Windows XP Pro / WEPOS / POSReady / Win 7 / Linux / Win Vista		Windows XP Pro / WEPOS / POSReady / Win 7 / Win Vista			
Display						
LCD	17" TFT LCD, 1280 x 1024 resolution		15" TFT LCD, 1024 x 768 resolution		17" TFT LCD, 1280 x 1024 resolution	
Touch Function	Resistive, 5-wire, USB Interface	IR touch	Resistive, 5-wire, USB Interface	IR touch	Resistive, 5-wire, USB Interface	IR touch
Brightness Control	By digital push button or software control					
Tilt Adjustment	From 15° to 75°					
Connectivity						
LAN Port	10 / 100 / 1000 Mb					
Parallel Port	1					
Serial Port	DB9 x4, with 5V support on COM1/COM2/COM3/COM4					
UPS Port	Yes, Battery (Optional)					
Standard USB Port	6					
Proprietary USB Port	1 for side mount (Optional)					
VGA Port	D-SUB 15 Pin, with 12V power for Posiflex LCD Monitor					
CR Port	1, Control 2 CR					
Physical Dimension						
Dimension (W x D x H in mm)	426 x 326 x 418		378 x 321 x 362		426 x 326 x 418	
Weight (N. W. in kg)	12.5		9.7		12.5	
Environment						
Operation Condition	0°C - 40°C, 20%RH - 90%RH					
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH					
Options						
PD-305	N/A		2 x 20, LCD, rear top mount		N/A	
PD-306 / PD-306U	N/A		2 x 20, LCD, default 200 mm pole		N/A	
PD-309 / PD-309U			2 x 20, LCD, default 200 mm pole			
PD-310 / PD-310U			2 x 20, LCD, rear top mount			
PD-2602 / PD-2602U	N/A		2 x 20, VFD, default 200 mm pole		N/A	
PD-2604 / PD-2604U			2 x 20, VFD, rear top mount			
PD-2605 / PD-2605U			2 x 20, VFD, default 200 mm pole			
PD-76X2	N/A		240 x 64 dots Graphics LCD, default 200 mm pole		N/A	
PD-76x4			240 x 64 dots Graphics LCD, default 200 mm pole			
CF Kit	Bracket & Cable & Module					
CF Card	Type I Only					
UPS Battery	2300 mAh/12V					
2nd HDD	Yes					
MSR	SD-400W/SD-400T, 2 or 3 tracks or JIS-II or Finger print sensor (Optional), SD-600, iBotton or 2 or 3 tracks and JIS-II (Optional) SD-800, 2 or 3 tracks or JIS-II or RFID (Optional) or WiFi (Optional)					
KP-300W-R	36 Key plus lock keypad or MSR (Optional) or Card reader (Optional)					
2nd LCD Display	12" LM-6101B, 15" LM-6501B		12" LM-6101B, 15" LM-6501B/LM-8015B		12" LM-6101B, 15" LM-6501B	
Certifications						

KS-7300 / 6600 Series

Scalable Fan-Free POS Terminal /
Middle-Range Fan-Free POS Terminal



Design and Manufacturing In Taiwan by Posiflex Technology Inc.
** The product information and specifications are subject to change without prior notice.

2011 KS7366Q1C1

POSIFLEX Posiflex Technology, Inc.
Head Quarter
6, Wu-Chuan Road, Wu Ku, Taipei, Taiwan
Tel: +886 2 2299-1599 Fax: +886 2 2299-1819
sales@posiflex.com.tw www.posiflex.com

Authorized Distributor / Reseller

www.posiflex.com

KS-7300 / 6600 Series

Posiflex reveals the KS-7300 series as a scalable POS terminal even in a fan-free design; while the KS-6600 series as a middle-range one.

The KS-7300 / 6600 series take pride in streamlined and patented aluminum die casting design, resistive (Or IR) touch screen, as well as UPS functions. The built-in UPS function is embedded on main board developed by Posiflex for better stability than others.

The KS-7300 / 6600 series support Intel Core 2 Duo 2.16 GHz / Celeron-M1.5 GHz CPU respectively, and 17" or 15" LCD in a small footprint. Above all, the KS-7300 series is among the world 1st fan-free Core 2 Duo POS terminal in a special thermal solution. The KS-7300 / 6600 series also support versatile peripheral options such as MSR, built-in CF memory card reader, and a wide range of connectivity to meet numerous applications.

The KS-7300 series is suitable for busy retailers to serve customers quickly.

The KS-6600 series is suitable for small and medium retailers to serve customers efficiently.



Key Features

- ▶ Resistive or IR touch screen : 17" LCD 1280 x 1024 or 15" LCD 1024 x 768 resolution
- ▶ Spill-resistant design to prevent careless spill and provide clean easily for a wide range of applications
- ▶ Equipped with Intel Core 2 Duo 2.16 GHz / Celeron-M1.5 GHz CPU for the KS-7300 / 6600 series, respectively
- ▶ Fan-free design boasting quiet and anti-dust features
- ▶ Patented aluminum die casting design for efficient cooling
- ▶ UPS (Embedded on board developed by Posiflex) to avoid sudden loss of power during transaction
- ▶ Patented finger lever "Gear Lock" to adjust the LCD tilt angle from 15° to 70° vertically
- ▶ Push-open cover to protect power switch from accidental shutdown
- ▶ User-friendly mechanism for system upgrade and easy maintenance
- ▶ LCD panel brightness control by hardware buttons or software
- ▶ Bottom cable guide design and cover for safety and neat outlook
- ▶ Shiny diamond black, red or white front bezel for stunning look (KS-7315/6615 series)
- ▶ General 6 super slim base stand (Optional)

